

## // BLACKFOOT



### GENERAL DATA

Max. distance motor to the furthest socket. . . . . 30 m  
 Max. number of simultaneous users . . . . . 1  
 Estimated cleaning surface . . . . . 120 - 250 m<sup>2</sup>  
 Estimated sockets . . . . . 6 - 8

### UNIT SPECIFICATIONS

Primary filtration . . . . . Paper bag  
 Secondary filtration . . . . . Foamfilter  
 Capacity dust container . . . . . 12 L  
 Dimensions (W x H x D) . . . . . 0,32 x 0,63 x 0,32  
 Dimensions - installed. . . . . 0,60 x 0,90 x 0,60  
 Weight . . . . . 7,3 Kg  
 Number of motors. . . . . 1

### MOTOR SPECIFICATIONS

General. . . . . 220 - 250 VAC, 50 Hz  
 Power (nom.) . . . . . 1400 W  
 Power (max.) . . . . . 1600 W  
 Max. current. . . . . 6,5 A  
 Revolutions (max.) . . . . . 44617 / min  
 Fuse rating . . . . . 8 A  
 Motorframe . . . . . 139 mm  
 Carbon brushes. . . . . Ref. I.0710.1002  
 Motor control . . . . . 12VDC signal with safety transformer (VDEO551 - relay 16A)  
 Softstart . . . . . Yes

### TURBINE SPECIFICATIONS

Motor type. . . . . Through Flow  
 Number of stages . . . . . 1  
 Negative pressure. . . . . 3100 mm H<sub>2</sub>O  
 Max. airflow. . . . . 51,6 L/sec  
 Airwatts . . . . . 587 W

### AVAILABILITY

I.0027.1000. . . . . Central vacuum unit Blackfoot

### CERTIFICATION

CE . . . . . Conform

Technical data is subject to change without notice.  
 Please check our website for latest information.